

New ML Diva Series

Diva in name.
Diva in fact.



Rizzoli 



NEW ML DIVA SERIES.
THE CHARM OF WOOD COOKING.

ML 60 Diva

The range of the already articulated M Series expands with the arrival of the New ML Diva Series, a wood cooker available in two sizes (60 and 80 cm wide) which features a decisive character and an aesthetic charm that does not leave indifferent.

ML Diva combines the elegant and gentle soul of the chromium plating of handles and handrails, with the robust and armored appearance of its imposing structure, the result of the use of ancient methods of construction that Rizzoli used in the 1930s.

The Velvety satin finish is very special and exclusive Steel® of the quay steel, obtained thanks to a totally artisanal procedure. The result is a unique wood-burning cooker, capable of enhance the already extraordinary features of the M Series: unmatched vision of the fire, maxi combustion chamber, super large oven.

Extraordinary are also the technologies present in the wood cookers, thanks to which ML Diva has earned the best European certifications at low emissions level in atmosphere.



Certifications:



Certified technologies:





Rizzoli



ML 80 Diva



MAXI
FIRE
CHAMBER

MAXI
PANORAMIC
OVEN

EXCLUSIVE
TREATMENT
OF THE FRAME
VELVETY
STEEL®

OVEN WITH
DOUBLE
GLASS,
LIGHT AND
THERMOMETER

ALWAYS
COLD
ISOLATED
HANDLES

HIGH
QUALITY
REFRACTORY
MATERIAL

TECHNICAL SPECIFICATIONS

Model	Width	Depth	Height ⁽¹⁾	Top thickness	Top protrusion	Riser	Hotplate diameter	Combusti on chamber (average) value	Combusti on chamber (l/h)	Weight (Kg.)	Oven dimensions (lpxh)	Total nominal power (kW)	Efficiency at nom. power %	Discharge gas flow (g/s)	Discharge gas temperature (°C) ⁽²⁾	Suggested draught (Pa)
ML 60 Diva	600	600	900	30	20	40x15	238	250	300x196	180	350x470x260	8,0	80,2	10,0	191	10
ML 80 Diva	800	600	900	30	20	40x15	280	250	500x196	230	550x470x260	8,0	80,2	10,0	191	10

Dimensions in mm

(1) Over top dimension (riser excluded).

(2) Average temperature at nominal power. It is possible to obtain higher fumes temperatures. It is recommended to use only pipes with minimum specify T400.

ENDOWMENTS

Model	External air intake - External Air®	Certified combustion system Superflame®	Sys. for the safe built-in into furn. Surround Heat®	Primary air regulation	Pre-heated secondary air	Aerated sides with natural convecti on	Fire door with self-cleaning system Shiny Glass®	Fire door with double glass	Reversible fire door	Oven door with double glass and thermometer	Multiflue	Oven with electrical illuminati on	Telescopic pullout for baking pan	Always cold handles thermally isolated	Fire door protection	Frontal handrail	Lateral handrail	Plate cover	Spacers	Profiles for top	Glass ceramic plate ⁽¹⁾	Maintenance kit
ML 60 Diva	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥
ML 80 Diva	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥	🔥

🔥 standard
 🌿 on demand
 🔥 optional

(1) Only for wood fired cookers with rear flue outlet.

MODEL



ML 60 Diva

ML 80 Diva

Partner:



Rizzoli s.r.l. - Single seat

Zona Artigianale 1, - Frazione San Lugano - 39040 - Trodena nel Parco Naturale (BZ) - Italia
Tel. +39 0471 887551 - info@rizzolicucine.it - www.rizzolicucine.it



#rizzolicucine