



# RIZZOLI®

FIRE SINCE 1912

## DECLARATION OF PERFORMANCE

ACCORDING TO REGULATION (EU) 305/2011

### N. 133

|    |                                                                                                                           |                                                                                                                |
|----|---------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| 1. | Unique identification code of the product-type                                                                            | : XT                                                                                                           |
| 2. | Type, batch or serial number (Art. 11-4)                                                                                  | : T-BASIC BE - T-CHEF BE                                                                                       |
| 3. | Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification    | : Domestic heating solid fuel                                                                                  |
| 4. | Name or registered trademark of the manufacturer (Art. 11-5)                                                              | : Rizzoli S.r.l.                                                                                               |
| 5. | Name and address of the manufacturer                                                                                      | : ----                                                                                                         |
| 6. | System of assessment and verification of constancy of performance (Attachment 5)                                          | : System 3                                                                                                     |
| 7. | Notified laboratory                                                                                                       | : ACTECO s.r.l. - (N.B. 1880)<br>I-33084 Cordenons (PN)<br>Via Amman, 41<br>1880-CPR-073-19<br>1880-CPR-039-19 |
|    | Issued test report                                                                                                        | :                                                                                                              |
| 8. | <b>Declared performance</b>                                                                                               |                                                                                                                |
|    | Harmonized technical specification                                                                                        | : EN 13240:2001/A2:2004/AC:2007                                                                                |
|    | <b>Essential characteristics</b>                                                                                          | <b>Performance</b>                                                                                             |
|    | Reaction to fire                                                                                                          | : A1                                                                                                           |
|    | Distance to combustibile materials                                                                                        | : <b>Minimum distances, in mm:</b><br>rear = 100, sides = 50, floor = 0,<br>ceiling = --, front = 800          |
|    | Risk of burning fuel falling out                                                                                          | : Pass                                                                                                         |
|    | Emission of combustion products                                                                                           | : CO [0,08 %]                                                                                                  |
|    | Surface temperature                                                                                                       | : Pass                                                                                                         |
|    | Electrical safety                                                                                                         | : Pass                                                                                                         |
|    | Cleanability                                                                                                              | : Pass                                                                                                         |
|    | Maximum water operating pressure                                                                                          | : 3 bar                                                                                                        |
|    | Flue gas temperature at nominal heat output                                                                               | : T [199 °C]                                                                                                   |
|    | Mechanical resistance                                                                                                     | : NPD                                                                                                          |
|    | Nominal heat output                                                                                                       | : 9,1 kW                                                                                                       |
|    | Room heating output                                                                                                       | : 7,1 kW                                                                                                       |
|    | Water heating output                                                                                                      | : 2,0 kW                                                                                                       |
|    | Energy efficiency                                                                                                         | : η [85,1 %]                                                                                                   |
| 9. | The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.    |                                                                                                                |
|    | <b>This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.</b> |                                                                                                                |

Trodene n.P.N., October 21<sup>st</sup> 2019

