RIZZOLI®
FIRE SINCE 1912

DECLARATION OF PERFORMANCE

ACCORDING TO REGULATION (EU) 305/2011

N. 236

1.	Unique identification code of the product-type:		**RVE 80 B**		
	Model identifier / equivalent models:		**R 60 CF B - R 70 B - R 80 B - R 90 B - R 100 B**		
2.	Intended use/es:		**Cooking and space heating in residential buildings**		
3.	Name or registered trademark of the manufacturer:		**Rizzoli S.r.l.**		
4.	Authorized representative:		---		
5.	System of assessment and verification of constancy of performance:		**System 3**		
6.	Notified body:		**ACTECO s.r.l. - N.B. 1880** **Test report n. 1880-CPR-032TR-15 Rev01**		
7.	Harmonised standard:		**EN 16510-2-3:2022**		
8.	**Essential Characteristics**		**Performance**		
	Mechanical resistance and stability				
	Load bearing capacity		**0 kg**		
	Safety in case of fire				
	Protection and minimum distances to combustible materials	bottom floor in front ceiling rear side side radiation area front	**d_B = 0 mm** **d_F = 0 mm** **d_C = 700 mm** **d_R = 150 mm** **d_S = 3 mm** **d_L = 0 mm** **d_P = 500 mm**		
		Material type and thickness of protective insulation material	**NPD**		
	Hygiene, health and the environment				
			at nominal heat output	at part load heat output	
	Emissions	CO NOx OGC PM	**668 mg/Nm³** **127 mg/Nm³** **47 mg/Nm³** **39 mg/Nm³**	**NPD** **NPD** **NPD** **NPD**	
	Safety and accessibility in use				
			at nominal heat output	at part load heat output	
	Data for installation to a chimney	Flue gas outlet temperature Minimum flue draught Flue gas mass flow	**187 °C** **12 Pa** **8,5 g/s**	**NPD** **NPD** **NPD**	
		Fire safety	**T400 G**		
	Energy economy and heat retention				
			at nominal heat output	at part load heat output	
	Appliance's thermal output and energy efficiency	Space heat output Water heat output Efficiency	**7,9 kW** **NPD** **85,8 %**	**NPD** **NPD** **NPD**	
	Space heating efficiency				
		Seasonal space heating energy efficiency	**75,8 %**		
		Energy efficiency index (EEI)	**114,4**		
		Energy efficiency class	**A+**		
			at nominal heat output	at part load heat output	in standby mode
		Electric power consumption	**NPD**	**NPD**	**NPD**
	Sustainable use of natural resources				
	Environmental sustainability		**NPD**		
9.	The performance of the product identified above is in conformity with the set of declared performance/s. **This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.**				

Trodena n.P.N., June 10th 2026

RIZZOLI
FIRE SINCE 1912
Zona Artigianale, 1 - Frazione San Lugano
I - 39040 TRODENA (BZ)
Tel. +39 0471 887551
P. IVA e C.F. 00624200226