

DECLARATION OF PERFORMANCE

ACCORDING TO REGULATION (EU) 305/2011

N. 89

| 1. | Unique identification code of the product-type | : | RTVE 60 B |
|----|--|-----|--|
| 2. | Type, batch or serial number (Art. 11-4) | : | RTE 60 B - RTVE 60 B |
| 3. | Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification | : | Cooker burning and domestic heating solid fuel |
| 4. | Name or registered trademark of the manufacturer (Art. 11-5) | : | Rizzoli S.r.l. |
| 5. | Name and address of the manufacturer | : | |
| 6. | System of assessment and verification of constancy of performance (Attachment 5) | : | System 3 |
| 7. | Notified laboratory | : | ACTECO s.r.l (N.B. 1880) I-33084 Cordenons (PN) Via Amman, 41 |
| | Issued test report | : | 1880-CPR-005-16 |
| 8. | Declared performance | | |
| | Harmonized technical specification | : | EN 12815:2001/A1:2004/AC:2007 |
| | Essential characteristics | | Performance |
| | Reaction to fire | : | A1 |
| | Distance to combustible materials | : | Minimum distances, in mm: rear = 250, sides = 250, floor = 0, ceiling = 600, front = 800 |
| | Risk of burning fuel falling out | : | Pass |
| | Emission of combustion products | : | CO [0,12 %] |
| | Surface temperature | : | Pass |
| | Electrical safety | : | Pass |
| | Cleanability | : | Pass |
| | Maximum water operating pressure | : | 3 bar |
| | Flue gas temperature at nominal heat output | : | T [222,6 °C] |
| | Mechanical resistance | : | NPD |
| | Nominal heat output | | 11,1 kW |
| | Room heating output | : | 5,4 kW |
| | Water heating output | | 5,7 kW |
| | Energy efficiency | | η [83,3 %] |
| 9. | The performance of the product identified in point performance in point 8. | s 1 | and 2 is in conformity with the declared |
| | This declaration of performance is issued under t identified in point 4. | he | sole responsibility of the manufacturer |
| 1 | • | | |

Trodena n.P.N., February 08th 2016



