

DECLARATION OF PERFORMANCE

ACCORDING TO REGULATION (EU) 305/2011

N. 67

Unique identification code of the product-type
 Type, batch or serial number (Art. 11-4)
 STP B

Intended use or uses of the construction product,

in accordance with the applicable harmonised

technical specification

Name or registered trademark of the manufacturer

4. (Art. 11-5)

5. Name and address of the manufacturer

System of assessment and verification of constancy

of performance (Attachment 5)

7. Notified laboratory : I-33084 Cordenons (PN)
Via Amman, 41

Issued test report : 1880-CPR-021-15

8. Declared performance

Harmonized technical specification : EN 12815:2001/A1:2004/AC:2007

Essential characteristics Performance

Reaction to fire : A1

Minimum distances, in mm:

ACTECO s.r.l. - (N.B. 1880)

solid fuel

: Rizzoli S.r.l.

: System 3

Cooker burning and domestic heating

Distance to combustible materials : rear = 10, sides = 10, floor = 0,

ceiling = 700, front = 800

Risk of burning fuel falling out : Pass

Emission of combustion products : CO [0,11 %]

Surface temperature : Pass

Electrical safety : Pass

Cleanability : Pass

Maximum water operating pressure : 3 bar

Flue gas temperature at nominal heat output : T [201,9 °C]

Mechanical resistance: NPDNominal heat output11,3 kWRoom heating output: 4,7 kWWater heating output6,5 kWEnergy efficiency: η [80,3 %]

The performance of the product identified in points 1 and 2 is in conformity with the declared

performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Trodena n.P.N., June 12th 2015



