

T:
@:

RI RANGE WITH OVEN - RI 70

TECHNICAL SPECIFICATIONS

- *Surround Heat*® insulated system for Built-in Appliances
- Adjustable Height Kitchen*: 850 - 920 mm (excluding upstand 60x15mm - HxD)
 - with 30 mm thick top: height 850 - 910 mm
 - with 40 mm thick top: height 860 - 920 mm
- Height and Width Adjustable Plinth
- 30 or 40 mm Stainless Steel Top
- Steel or Glass ceramic radiant plate
- Horizontally and vertically adjustable rear flue outlet
- Side Flue Outlet with Telescopic Pipe
- *Soft close* wood cushioned box
- Vent to the Outside
- Airtight Fire Door
- Combustion chamber made of Certified refractory material
- *Superflame*® Certified combustion system
- Primary and Secondary Air automatic regulation
- Pre-heated Secondary Air
- Ignition with Bypass Key
- Regulation/Closing of vent to the outside
- Natural thermal convection on the sides
- Heat Transfer Ventilation
- Quick-release oven door with double-glazed glass
- Oven with Light and Thermometer
- Oven with Steam-conditioning valves
- Oven with Pyrolytic Coating
- Pyrolytic coated baking tray on Telescopic rails and Oven grill grid

TECHNICAL DATA

- **Length:** 700 mm
- **Total Nominal Power:** 8,0 kW
- **Adjustable Height*:** 850 - 920 mm
- **Nominal Power Performance:** 82,7%
- **Width:** 600 mm
- **Maximum Power:** 9,5 kW
- **Size of the Oven (lxhwx):** 250x260x430 mm
- **Weight:** 195 kg

RETRIEVE YOUR CONFIGURATION

Scan the QR CODE or copy the link below to retrieve your configuration.



<https://www.rizzolicucine.it/en/products/wood-burning-cookers/r-range/67/ri-70#configurator-67/0/0>

Configuration code : **ib7Yu9OQi**

26-03-2023