



RIZZOLI®

FIRE SINCE 1912

DECLARATION OF PERFORMANCE

ACCORDING TO REGULATION (EU) 305/2011

N. 231

1.	Unique identification code of the product-type:	X-TYPE B		
	Model identifier / equivalent models:	X-BASIC B - X-PLUS B - X-CHEF B X-VISION B - X-LIVING B - X-DATEO B		
2.	Intended use/es:	Space heating in residential buildings		
3.	Name or registered trademark of the manufacturer:	Rizzoli S.r.l.		
4.	Authorized representative:	---		
5.	System of assessment and verification of constancy of performance:	System 3		
6.	Notified body:	ACTECO s.r.l. - N.B. 1880 Test report n. 1880-CPR-017-26		
7.	Harmonised standard:	EN 16510-2-1:2022		
8.	Essential Characteristics	Performance		
	<i>Mechanical resistance and stability</i>			
	Load bearing capacity	0 kg		
	<i>Safety in case of fire</i>			
	Protezione e distanza minima da materiali combustibili	bottom floor in front ceiling rear side side radiation area front	d _B = 0 mm d _F = 400 mm d _C = 750 mm d _R = 150 mm d _S = 300 mm d _I = 700 mm d _P = 1250 mm	
	Material type and thickness of protective insulation material	NPD		
	Hygiene, health and the environment			
	Emissions	CO NOx OGC PM	at nominal heat output 732 mg/Nm ³ 106 mg/Nm ³ 91 mg/Nm ³ 12 mg/Nm ³	at part load heat output 1237 mg/Nm ³ 106 mg/Nm ³ 240 mg/Nm ³ 12 mg/Nm ³
	Safety and accessibility in use			
	Data for installation to a chimney	Flue gas outlet temperature Minimum flue draught Flue gas mass flow Fire safety	at nominal heat output 219 °C 12 Pa 5,3 g/s T400 G	at part load heat output 196 °C 10 Pa 4,9 g/s
	Energy economy and heat retention			
	Appliance's thermal output and energy efficiency	Space heat output Water heat output Efficiency	at nominal heat output 4,6 kW NPD 83,2 %	at part load heat output 3,1 kW NPD 80,3 %
	Space heating efficiency			
	Seasonal space heating energy efficiency	73,2 %		
	Energy efficiency index (EEI)	110,6		
	Energy efficiency class	A+		
	Electric power consumption	at nominal heat output NPD	at part load heat output NPD	in standby mode NPD
	Sustainable use of natural resources			
	Environmental sustainability	NPD		
9.	The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.			

Trodene n.P.N., February 18th 2026

 **RIZZOLI**
 FIRE SINCE 1912
 Zona Artigianale 1 - Frazione San Lugano
 I - 39040 TRODENA (BZ)
 Tel. +39 0471 887551
 P. IVA e C.F. 00624200226

Rizzoli srl - Unica sede - Zona Artigianale 1, Frazione San Lugano - 39040 Trodena nel Parco Naturale (BZ) - Italia
 Tel. +39 0471 887551 - info@rizzolicucine.it - www.rizzolicucine.it
 R.I. (BZ) - C.F. - P. IVA 00624200226 - Capitale sociale € 80.600 i.v. - rizzolicucine@pec.it

A company from
SÜDTIROL